<u>600SS</u>

Sheet 1 of 2

<u>STATE</u> <u>OF</u> <u>TENNESSEE</u>

(Rev. 5-18-15) January 1, 2015

Supplemental Specifications - Section 600

of the

Standard Specifications for Road and Bridge Construction

January 1, 2015

Subsection 604.03 (pg. 522 and 523), 5-18-15; 2. Mix Design Submittal; Replace the first sentence of the last paragraph on page 522 with the following: Instead of the above mix design submittal, an existing design may be submitted for approval provided the design has been used on a state funded project within the last six (6) months.

Sheet 2 of 2

Subsection 615.17 (pg. 652), 5-18-15; Table 615.17-1: Manufacturing Tolerances in Standard Sections, Replace the following:

Table 615.17-1: Manufacturing Tolerances in Standard Sections

Description	Tolerance	
	I-Sections	Box Sections
Nominal Depth	± 1/2 inch	± 1/2 inch
Nominal Width	± 1/2 inch	± 1/2 inch
Nominal Length	Computed Elastic Shortening ±1/2 inch	Computed Elastic Shortening ±1/2 inch
Variation in Straightness, inches	1/4 inch x (Total Length in feet)/10	1/4 inch x (Total Length in feet)/10
Variation in Camber, inches	Beams in any 1 span not more than: 1/8 inch x (Total Length in feet)/10	Beams in any 1 span not more than: 1/8 inch x (Total Length in feet)/10
Location of Voids		Length $\pm 1/2$ in Wall Thickness $\pm 1/2$ in
Bearing	Full Bearing - Full Width of Beam	Full Bearing on at Least 2/3 of Width of Beam
Tendon Placement	± 1/2 inch	± 1/2 inch
Reinforcing Steel Placement	± 1/2 inch	± 1/2 inch
Reinforcing Steel Concrete Cover	± 1/2 inch	± 1/2 inch
Reinforcing Steel Splice Lengths	Minus 1-1/2 inches	Minus 1-1/2 inches